

RX26-Z

A complete range of radio control and switching products to provide wire-free control of gates, barriers, doors, lights etc. A high quality and a high performance range.

The external receiver range is compatible with all our rolling-code transmitters. The receivers are available in various formats, including low or high voltage input and different relay outputs with combinations of pulse, latched and timed triggers - please consult with CDVI technical for full details.

All external receivers are housed in weather resistant enclosures, and are ideal for the control of external gates, barriers and lighting.

Standard range is up to 200 metres, this can be enhanced by installing the optional SEA433 tuned aerial.



RX26-Z1



RX26-Z2



RX26-Z4

Overview

- External rated receivers
- 1, 2 & 4 channel
- 12-24V ac/dc option
- Relay pulse, timed and latch
- Extension tuned aerial (SEA433)
- Encoding: Keeloq hopping code

RX26-Z - Technical Specifications

Product Specifications

Memory capacity: 85 transmitters
Demodulation: ASK
Frequency: 433.92 Mhz
Encoding: Keeloq hopping code

Electrical Specifications

Power supply: 12 to 24Vac/dc

Relays

RX26-Z1: 1 relay
RX26-Z2: 2 relays
RX26-Z4: 4 relays

Dimensions

Dimensions: 80 x 80 x 50mm