

## (1) EU-Type-Examination Certificate

- (2) Equipment and protective systems intended for use in potentially explosive atmospheres, **Directive 2014/34/EU**



- (3) **Certificate Number** TÜV CY 24 ATEX 0207256 X
- (4) for the equipment: Magnetic contact  
Type: MCX270-\*\*\*\*
- (5) of the manufacturer: **ALARMTECH Sweden AB**
- (6) Address: Staffans Väg 6A, S-192 78 Sollentuna, Sweden
- Order number: 0207256
- Date of issue: 2025-02-24


- (7) The design of this equipment or protective system and any acceptable variation thereto are specified in the schedule to this EU-Type-Examination Certificate and the documents therein referred to.
- (8) TÜV CYPRUS Ltd, notified body No. 2261 in accordance with Article 17 of the Council Directive of 2014/34/EU of February 26, 2014, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive. The examination and test results are recorded in the confidential report No. 24 0207256.
- (9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:  
**EN IEC 60079-0:2018                      EN 60079-18:2015                      EN 60079-18:2015/A1:2017**
- (10) If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This EU-Type-Examination Certificate relates only to the design, examination and tests of the specified equipment in accordance to the Directive 2014/34/EU. Further requirements of the Directive apply to the manufacturing process and supply of this equipment which are not covered by this certificate.
- (12) The marking of the equipment or protective system must include the following:

 **II 1G Ex ma IIC T6 Ga**

TÜV CYPRUS Ltd (TUV NORD Group),

The head of the notified body,

D. Demosthenous



Accredited by CYS-CYSAB  
Certificate No. C 004-3

TÜV CYPRUS (TÜV NORD) Ltd,  
2 Papaflessa Str., 2235 Latsia, Nicosia - P.O.Box: 20732, 1663 Nicosia, Cyprus  
Tel: +357 22 44 28 40 Fax: +357 22 44 28 50 email: [info@tuvcyprus.com.cy](mailto:info@tuvcyprus.com.cy)  
[www.tuv-nord.com/cy](http://www.tuv-nord.com/cy)

This certificate may only be reproduced without any change, schedule included.  
Excerpts or changes shall be allowed by the TÜV CYPRUS Ltd

## (13) SCHEDULE

## (14) EU-Type-Examination Certificate No. TÜV CY 24 ATEX 0207256 X

### (15) Description of equipment

The MCX270-\*\*\*\* is a high security heavy duty magnetic contact used in both alarm and security access control systems for protection of garage doors, industrial gates etc. against unauthorised opening. The electronic board is contained inside a metallic enclosure and encapsulated with an epoxy compound. MCX270-\*\*\*\* has an extra sabotage reed switch to protect the contact from sabotage with an external magnet. The equipment is provided with a permanently connected cable, encapsulated to the enclosure. The type of protection is by encapsulation "Ex ma" and the equipment is suitable for gas Group IIC.

### Type code identification:

This certificate covers the magnetic contact type MCX270-\*\*\*\*. The asterisks in this document are used in place of one or more optional character(s) concerning additional information about the equipment, as specified in the following table:

MCX270	-*	***	
			Magnetic contact with two reed switches
			Blank space: no resistors -R : 1 resistor -2R : 2 resistors
			Resistance value (kOhm)

### Technical data:

The equipment must be connected by means of the cable leads to a power supply circuit with a maximum rated voltage according to the following table, and protected by a suitable fuse installed between the equipment and the power supply.

Model	Resistor (Ohm)	Max supply voltage (V)	In fuse (max) (mA)
MCX270	/	48	294
MCX270-R1k	1000	18.5	18.5
MCX270-R2,2k	2200	27.5	12.5
MCX270-R4,7k	4700	40.5	8.5
MCX270-R5,6k	5600	44	8
MCX270-R6,8k	6800	48	7
MCX270-R10k	10000	48	6
MCX270-R16,2k	16200	48	4.5



Model	Resistor (Ohm)	Max supply voltage (V)	In fuse (max) (mA)
MCX270-2R1k	1000	13	13
MCX270-R2,2k	2200	19.5	9
MCX270-R4,7k	4700	28.5	6
MCX270-R5,6k	5600	31	5.5
MCX270-R6,8k	6800	34.5	5
MCX270-R10k	10000	41.5	4
MCX270-R16,2k	16200	48	3.3

## Ratings:

The fuse shall comply with IEC 60127 or ANSI/UL 248 series. The short-circuit breaking capacity of the fuse shall be minimum 1500 A with rated voltage equal to or higher than the rated voltage of the equipment.

## Allowable ambient temperature range:

T.amb.:  $-40^{\circ}\text{C} \leq T_a \leq +70^{\circ}\text{C}$

## Warning labels:

None

(16) Test documents are listed in the test report No. 24 0207256

(17) Special conditions for safe use

- The equipment shall be protected by a suitable external fuse as indicated in technical data and in the safety instruction.
- The device has a permanently connected cable. The free end of the cable has to be connected in an enclosure made in one or more of types of protection listed in EN 60079-0 and compatible with the classification of the hazardous zone, or it has to be connected outside of the hazardous area.

(18) Essential Health and Safety Requirements

This EU type-examination certificate covers only the Essential Health and Safety Requirements related to the Directive 2014/34/EU. No additional ones.