



Flush Magnetic Contact

Code: FC620/WH

FC620 4 Wire | Flush Contact | Grade 2 | White | Non-resistored

This flush mounted magnetic door contact can be used in most security systems up to and including grade 2 as specified in EN50131-1: 2006 and is compliant to EN50131-2-6:2008 and environmental class II (for use indoors). It operates as a normally closed circuit going open when the magnet is removed. This contact can be used on most doors to detect the unauthorised entry of an intruder.

Features & Benefits

- 4 Core pre-wired
- Suitable for metal doors or window applications
- Double pole configuration
- Suitable for domestic and commercial alarm circuits
- High impact polymer construction
- · Grade 2 Environmental Class II



CQR Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH

Sales: +44(0)151 6061000 (9am to 5pm Monday to Friday) **Tech:** +44(0)151 606 6311

sales@cqr.co.uk | www.cqr.co.uk

Company Registration Number: 5192024 | VAT Number: 309 0409 27





Product Information

Product information	
Connection type	Wired
Security	
EN50131-2-6 Grade	2
Tamper Protection	Internal
Environmental	
EN50130-5 class	Class II
IP Rating	3X
Temperature range	-10°C - +40°C
Housing	
Colour	White

HIPS

9.5Ø x 31.5

9.5Ø x 31.5

El		- 4			-
	Δ	\sim T	rı	\sim	١I
		97 1	ш	٠,ر	11
	\smile			-	41

Material

Contact Dimensions (mm)

Magnet Dimensions (mm)

Connection type	Wired
No. of terminals	4 Wire
Contact type	Normally Closed
Contact Material	Palladium
Wire length (mm)	250

Features

Mode of operation	DP
Operation Axes (X, Y, Z)	Y, Z
Pull-in gap (X, Y, Z)mm	25, 25
Suitable for Double Door	Yes
No. of terminals	4 Wire

CQR Security, 125 Pasture Road, Moreton, Wirral, CH46 4TH

Sales: +44(0)151 6061000 (9am to 5pm Monday to Friday) **Tech:** +44(0)151 606 6311

sales@cqr.co.uk | www.cqr.co.uk

Company Registration Number: 5192024 | VAT Number: 309 0409 27

