

SLIM-R-DUAL

SLIM-R-DUAL is an indoor motion detector from the SLIM LINE series, designed for recessed ceiling mounting. Is it an excellent solution for rooms with suspended ceilings. With its 360 ° detection coverage, it is well suited for monitoring shops, warehouses, and other spaces where a ceiling-mounted detector facing downward provides more effective area coverage than a wall-mounted detector.

This model is also available for surface mounting (**SLIM-S-DUAL**).

- compliant with the **EN 50131 Grade 2** requirements
- motion detection using two sensors: passive infrared (PIR) and microwave (MW)
- maximum detection area:
 - \varnothing 6 m / 28 m² – mounting height 2,4 m
 - \varnothing 10 m / 79 m² – mounting height 3,5 m
- detector operating parameter configuration: on-board buttons
- digital motion detection algorithm for both sensors
- digital temperature compensation
- adjustable detection sensitivity for both sensors
- separate sensor testing feature
- digital filtering of signals received by the microwave sensor, ensuring immunity to interference caused by the power grid and discharge lamps
- built-in EOL resistors: 1,1 k Ω
- LED indicator:
 - selectable alarm indication color (7 colors available)
 - remote on/off control
- remote enable/disable of configuration mode
- supervision of the motion detection circuit
- 12 V DC power supply (15%)
- power supply monitoring
- tamper protection against enclosure opening
- installation in suspended ceiling



Environmental class according to EN50130-5	II
EOL resistors	2 x 1,1 k Ω
Relay contact resistance (alarm output)	26 Ω
Tamper outputs (NC)	100 mA / 30 V DC
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Warm-up period	30 s
Security grade according to EN50131-2-4	Grade 2
Microwave frequency	24,125 GHz
Complied with standards	EN 50131-1, EN 50131-2-4, EN 50130-4, EN 50130-5
Alarm signaling time	2 s
Supply voltage	12 V DC
Dimensions	\varnothing 130 x 42 mm
Maximum humidity	93 \pm 3%
Weight	141 g
Max. current consumption	43 mA
Standby mode current consumption	12 mA
Recommended mounting height	2,4...3,5 m
Operating temperature range	-10°C...+55°C
Detected target velocity	0,3...3 m/s